



Article Number: 1.52.221

Product Range

Safety equipment

Product Category

INSULATED, GALVANISED VERSION:

Outer dim.: 1950 x 2350 x 2340(WxDxH in mm)

Inner dim.: 1772 x 2062 x 2051 (WxDxH in mm)

Capacity: 6300 l

Approval for storage of water polluting liquids

WGK 1 - 3, flammable liquids, F+, F outdoors or in building in accordance with the specific fire protection regulations.

Construction of container:

- Wall and ceiling elements made from galvanised trapezoidal sections, floor sections made from sheet steel.
- 1 leaf, galvanised door, 1294 mm wide and 1996 mm high, the door is hung on the right, mounted on the longitudinal side.
- Single-point locking
- Mortise lock with door handles and security lock with 2 keys.
- The accessible roof is designed for 125 kg/m² snow load.
- Drainage through inner-lying gutters.
- Bottom tray made from 3 mm thick, galvanised sheet steel, welded liquid-tight, covered with PE-foil.
- Standing level made from galvanised, removable

gratings, load 1000 kg/m².

- Walls, roof and door thermally insulated with insulation panels (45 mm).

Testing:

General national technical approval Z-38.5-94 of the Deutsche Institut für Bautechnik (DIBt) Berlin

Retail category	Safety storage container
Outer width	2350 mm
Outer depth	1950 mm
Outer height	2340 mm
Weight (product)	680 kg