Technical data sheet



02.06.2025 04:09



Sheet steel vanished in RAL XXXX Outer dim.: 2350 x 4020 x 2340 (LxWxH in mm) Inner dim.: 2152 x 3935 x 2051 (LxWxH in mm) Capacity: 10000 I Approval for storage of water polluting liquids

WGK 1 - 3, flammable liquids, F+, F outdoors or in building in accordance with the specific fire protection regulations.

Construction of container:

- Wall and ceiling elements made from galvanised trapezoidal sections, floor sections made from sheet steel.

- 1 leaf, galvanised door,

1294 mm wide and 1996 mm high,

the door is hung on the right,

mounted on the longitudinal side

(optionally on the longitudinal or narrow side).

- Single-point locking

- Mortise lock with door handles and security lock with 2 keys.

- The accessible roof is designed for 125 kg/m2 snow load.

- Drainage through inner-lying gutters.

- Bottom tray made from 3 mm thick, galvanised sheet steel, welded liquid-tight.

- Standing level made from galvanised, removable gratings, load 1000 kg/m2. Testing:

General national technical approval Z-38.5-94 of the Deutsche Institut für Bautechnik (DIBt) Berlin

Product Range Product Category Safety equipment

Technical data sheet



02.06.2025 04:09

Retail category	Safety storage container
Outer width	4020 mm
Outer depth	2350 mm
Outer height	2340 mm
Weight (product)	810 kg