



## UTS line

Article Number: 29-060667-003

**Product Range**

Safety storage cabinet

**Product Category**

Type 90 - flammable liquids

## General

<b>Line</b>	UTS
<b>Version</b>	pro
<b>Size</b>	S
<b>Type</b>	90
<b>Storage type</b>	passive storage
<b>Functionality</b>	Storage
<b>Earthing connection</b>	Yes
<b>Connection socket</b>	Yes

## Test criteria and documentation

<b>TÜV Süd certificate no.</b>	Z1A 012906 0521
<b>TÜV-Süd certificate type</b>	GS
<b>TÜV-Süd High Quality Zertifikat</b>	Z2 012906 0513
<b>DIN EN 14470-1</b>	Yes
<b>DIN EN 16121/16122</b>	Yes
<b>CE conformity</b>	Yes

## Technical specifications

<b>Outer width approx.</b>	601 mm
<b>Outer depth approx.</b>	594 mm
<b>Outer height approx.</b>	631 mm
<b>Max. load bearing capacity per storage area</b>	45 kg
<b>Max. load</b>	45 kg
<b>Max. total weight</b>	160 kg
<b>Max. volume of single container</b>	10 L
<b>Collection volume</b>	11,3 L
<b>Weight (product) approx.</b>	115 kg

## Cabinet

<b>Material of cabinet cladding</b>	Sheet steel
<b>Cabinet colour</b>	RAL 7035
<b>Material of inner lining</b>	Decor panels
<b>Colour of inner lining</b>	RAL 7035
<b>Base</b>	Classical
<b>Base height approx.</b>	35 mm
<b>Base colour</b>	RAL 7015

## Doors

<b>No. of doors</b>	1
<b>Kind of door</b>	Wing door
<b>Material of door cover</b>	Sheet steel
<b>Door colour</b>	RAL 1018
<b>Door hinge</b>	Right
<b>Door operation</b>	Classical
<b>Door technology</b>	Classical
<b>Door handle</b>	Bow handle matt nickel
<b>Lock</b>	Cylinder lock
<b>Locking system</b>	Open
<b>Locking points</b>	1-point

## Interior fittings

<b>Material of interior fittings</b>	Sheet steel
<b>Colour of interior fittings</b>	RAL 7035
<b>Bottom tray</b>	Extendable
<b>Bottom tray insert</b>	Perforated sheet insert
<b>Storage levels</b>	1
<b>Storage areas</b>	1
<b>setting height approx.</b>	340 mm