# Technical datasheet

30.10.2026 06:07



## UTS line

Article Number: 29-061159-003

| | |
|---|---|
| **Product Range** | Safety storage cabinet |
| **Product Category** | Type 90 - flammable liquids |

## General

| | |
|---|---|
| **Line** | UTS |
| **Version** | pro |
| **Size** | L-5 |
| **Type** | 90 |
| **Storage type** | passive storage |
| **Functionality** | Storage |
| **Earthing connection** | Yes |
| **Exhaust air connection** | Yes |

## Test criteria and documentation

| | |
|---|---|
| **TÜV Süd certificate no.** | Z1A 012906 0521 |
| **TÜV-Süd certificate type** | GS |
| **TÜV-Süd High Quality Certificate** | Z2 012906 0513 |
| **DIN EN 14470-1** | Yes |
| **DIN EN 16121/16122** | Yes |
| **CE conformity** | Yes |

## Technical specifications

| | |
|---|---|
| **Outer width approx.** | 1100 mm |
| **Outer depth approx.** | 494 mm |
| **Outer height approx.** | 631 mm |
| **Max. load bearing capacity per storage area** | 40 kg |
| **Max. load** | 40 kg |
| **Max. total weight** | 205 kg |
| **Weight (product) approx.** | 165 kg |
| **Max. volume of single container** | 16 L |
| **Collection volume** | 18,3 L |

## Cabinet

| | |
|---|---|
| **Material of cabinet cladding** | Sheet steel |
| **Cabinet colour** | RAL 7035 |
| **Material of inner lining** | Decor panels |
| **Colour of inner lining** | RAL 7035 |
| **Base** | Classical |
| **Base height approx.** | 35 mm |
| **Base colour** | RAL 7015 |

## Doors

| | |
|---|---|
| **No. of doors** | 2 |
| **Kind of door** | Wing door |
| **Material of door cover** | Sheet steel |
| **Door colour** | RAL 1018 |
| **Door operation** | One-hand |
| **Door technology** | Push-to-open |
| **Lock** | Cylinder lock |
| **Locking system** | Open |
| **Locking points** | 1-point |

## Interior fittings

| | |
|---|---|
| **Material of interior fittings** | Sheet steel |
| **Colour of interior fittings** | RAL 7035 |
| **Bottom tray** | Extendable |
| **Bottom tray insert** | Perforated sheet insert |
| **Storage levels** | 1 |
| **Storage areas** | 1 |
| **setting height approx.** | 340 mm |