



UTS line

Article Number: 29-061167-003

Product Range

Safety storage cabinet

Product Category

Type 90 - flammable liquids

General

Line	UTS
Version	pro
Size	L
Type	90
Storage type	passive storage
Functionality	Storage
Earthing connection	Yes
Connection socket	Yes

Test criteria and documentation

TÜV Süd certificate no.	Z1A 012906 0521
TÜV-Süd certificate type	GS
TÜV-Süd High Quality Zertifikat	Z2 012906 0513
DIN EN 14470-1	Yes
DIN EN 16121/16122	Yes
CE conformity	Yes

Technical specifications

Outer width approx.	1100 mm
Outer depth approx.	594 mm
Outer height approx.	631 mm
Max. load bearing capacity per storage area	45 kg
Max. load	45 kg
Max. total weight	230 kg
Max. volume of single container	21 L
Collection volume	23,9 L
Weight (product) approx.	185 kg

Cabinet

Material of cabinet cladding	Sheet steel
Cabinet colour	RAL 7035
Material of inner lining	Decor panels
Colour of inner lining	RAL 7035
Base	Classical
Base height approx.	35 mm
Base colour	RAL 7015

Doors

No. of doors	2
Kind of door	Wing door
Material of door cover	Sheet steel
Door colour	RAL 1018
Door operation	One-hand
Door technology	Classical
Door handle	Bow handle matt nickel
Lock	Cylinder lock
Locking system	Open
Locking points	1-point

Interior fittings

Material of interior fittings	Sheet steel
Colour of interior fittings	RAL 7035
Bottom tray	Extendable
Bottom tray insert	Perforated sheet insert
Storage levels	1
Storage areas	1
setting height approx.	340 mm