

UTS line

Article Number: 29-061159-005

Product Range	Safety storage cabinet
Product Category	Type 90 - flammable liquids

The safety storage cabinets of the UTS line are specially constructed for the storage of hazardous substances close to where they are needed. With the UTS line, all containers are always safely stored and at your fingertips when you need them.

- **Health**
Ideal layout of ventilation ensures an optimised air exchange.
- **Safety**
In case of fire, a thermocouple automatically initiates the uninterrupted closing of the doors.
- **Working safety**
Equipotential bonding saddles as a standard on the cabinet help to prevent spark formation.

Line	UTS
Type	90
Storage type	passive storage
Functionality	Storage
Earthing connection	Yes
Connection socket	Yes
TÜV-Süd certificate type	GS
DIN EN 14470-1	Yes
DIN EN 16121/16122	Yes
CE conformity	Yes
Outer width approx.	1100 mm
Outer depth approx.	494 mm
Outer height approx.	631 mm
Max. load bearing capacity per storage area	40 kg

Material of cabinet cladding	Sheet steel
Cabinet colour	RAL 7035
Base	Classical
Base height approx.	35 mm
Base colour	RAL 7015
Kind of door	Wing door
Door colour	RAL 1018
Lock	Cylinder lock
Locking system	Open
Material of interior fittings	Sheet steel
Centre partition wall	Yes
Bottom tray	Extendable
Bottom tray insert	Perforated sheet insert
Storage levels	1
Storage areas	2
setting height approx.	340 mm