

## UTS line

Article Number: 29-061459-005

<b>Product Range</b>	Safety storage cabinet
<b>Product Category</b>	Type 90 - flammable liquids

The safety storage cabinets of the UTS line are specially constructed for the storage of hazardous substances close to where they are needed. With the UTS line, all containers are always safely stored and at your fingertips when you need them.

- **Health**  
Ideal layout of ventilation ensures an optimised air exchange.
- **Safety**  
In case of fire, a thermocouple automatically initiates the uninterrupted closing of the doors.
- **Working safety**  
Equipotential bonding saddles as a standard on the cabinet help to prevent spark formation.

<b>Line</b>	UTS
<b>Type</b>	90
<b>Storage type</b>	passive storage
<b>Functionality</b>	Storage
<b>Earthing connection</b>	Yes
<b>Connection socket</b>	Yes
<b>TÜV-Süd certificate type</b>	GS
<b>DIN EN 14470-1</b>	Yes
<b>DIN EN 16121/16122</b>	Yes
<b>CE conformity</b>	Yes
<b>Outer width approx.</b>	1400 mm
<b>Outer depth approx.</b>	494 mm
<b>Outer height approx.</b>	631 mm
<b>Max. load bearing capacity per storage area</b>	40 kg

<b>Material of cabinet cladding</b>	Sheet steel
<b>Cabinet colour</b>	RAL 7035
<b>Base</b>	Classical
<b>Base height approx.</b>	35 mm
<b>Base colour</b>	RAL 7015
<b>Kind of door</b>	Wing door
<b>Door colour</b>	RAL 1018
<b>Lock</b>	Cylinder lock
<b>Locking system</b>	Open
<b>Material of interior fittings</b>	Sheet steel
<b>Centre partition wall</b>	Yes
<b>Bottom tray</b>	Extendable
<b>Bottom tray insert</b>	Perforated sheet insert
<b>Storage levels</b>	1
<b>Storage areas</b>	2
<b>setting height approx.</b>	340 mm