

## SUPPLY line

Article Number: 49-200977-032

|                         |                             |
|-------------------------|-----------------------------|
| <b>Product Range</b>    | Safety storage cabinet      |
| <b>Product Category</b> | Type 90 - flammable liquids |

The SUPPLY line Type 90 from DÜPERTHAL is specially designed to safely remove media from drums. This allows integration into present process chains and a more efficient organisation of the internal value chain. All SUPPLY line cabinets have a wide range of additional functions that make working easier and safer.

- **Technical ventilation**

Ventilation and exhaust air monitoring minimise the explosive atmosphere when filling.

- **Safety**

Safe media supply and integration into the process chain in accordance with TRGS 509 (active storage).

- **Working safety**

Conductive powder coating as a standard and integrated earthing system according to TRGS 727.

- **Monitoring with DÜPERTHAL connect**

Including hardware for monitoring fill level and prepared for online use of monitoring data in the DÜPERTHAL connect app.

|                                 |                           |
|---------------------------------|---------------------------|
| <b>Line</b>                     | SUPPLY                    |
| <b>Type</b>                     | 90                        |
| <b>Storage type</b>             | active storage - prepared |
| <b>Functionality</b>            | Storage                   |
| <b>Earthing connection</b>      | Yes                       |
| <b>Connection socket</b>        | Yes                       |
| <b>TÜV-Süd certificate type</b> | GS                        |
| <b>DIN EN 14470-1</b>           | Yes                       |
| <b>DIN EN 16121/16122</b>       | Yes                       |
| <b>CE conformity</b>            | Yes                       |

|  |                              |
|--|------------------------------|
| <b>Outer width approx.</b>                         | 894 mm                       |
| <b>Outer depth approx.</b>                         | 747 mm                       |
| <b>Outer height approx.</b>                        | 2045 mm                      |
| <b>Max. load bearing capacity per storage area</b> | 250 kg                       |
| <b>Potential-free contact</b>                      | Yes                          |
| <b>Material of cabinet cladding</b>                | Sheet steel                  |
| <b>Cabinet colour</b>                              | electrically conductive gray |
| <b>Base</b>  | Classical                    |
| <b>Base height approx.</b>                         | 89 mm                        |
| <b>Base colour</b>                                 | RAL 7015                     |
| <b>Kind of door</b>                                | Wing door                    |
| <b>Door colour</b>                                 | electrically conductive blue |
| <b>Door handle</b>                                 | Bow handle matt nickel       |
| <b>Lock</b>  | Cylinder lock                |
| <b>Locking system</b>                              | Open                         |
| <b>Material of interior fittings</b>               | Sheet steel                  |
| <b>Bottom tray</b>                                 | Fixed                        |
| <b>Bottom tray insert</b>                          | Grating                      |
| <b>Storage levels</b>                              | 1                            |
| <b>Storage areas</b>                               | 1                            |
| <b>setting height approx.</b>                      | 1177 mm                      |
| <b>Accessories</b>                                 | Yes                          |
| <b>Exhaust air monitoring</b>                      | yes w/display                |